



Easy Sand Acrylic Broad Wall Sealer

Easy Sand is primarily designed to seal interior plaster wall board. It has outstanding sanding qualities enhancing the quality of finish that can be achieved with the top coat. Easy Sand is very viscous until stirred and/or application forces of brushing, rolling or spraying are applied. This helps to avoid unsightly lapping lines, spatter and sagging.

Product features

Very high solids content covers and fills minor surface imperfections

Easy to apply

Sands freely

Adheres to a broad range of surfaces replacing the need for multiple products

Typical areas of use

Paper faced wall board

Stopping repairs

Fibrous plaster

Skimmed plaster

Precautions

Not to be used in exterior applications.

Easy Sand is extremely free sanding; care must be taken not to expose the substrate.

Environmental qualities

Manufactured in a carbon neutral certified facility – ISO 14064-1

VOC 2 gms per litre EC07-13

Ecolabel certified – Environmental Choice EC07-13
Licence number 0703012

Colour

Standard colour is white, may be tinted to light pastel colours.

Safety

Read label before use and keep out of reach of children.

If medical advice is needed: have product container or label at hand.

Wear protective clothing such as overalls, goggles and gloves and ventilate working areas.

Wash any paint deposits off skin.

If sanding wear face mask to avoid inhaling dust particles.

Surface preparation

General preparation of the surface to be painted should be completed before commencing application.

All loose material must be removed and surface damage or imperfections made good.

The surface must be clean, dry and free of contaminants.

Areas with a build up of grime must be cleaned with sugar soap or quality equivalent.

Previously painted enamel and polyurethane – sand to remove gloss and clean with a lint free cloth.

Application schedule

Touch dry 15 minutes

Re-coat time (minimum) 2 hours

Practical coverage 6–10 square meters per litre

Dry film thickness @ 10 square meters per litre
46 microns per coat

Required number of coats – 1

Application is not recommended if the surface and/or air temperature is less than 10°C or is liable to fall below 10°C during the drying period.

Application methods

Good quality paint or cutting in brush

Medium nap Roller – 12mm–14mm

Airless spray minimum 133 bars (2,000lb/sq in)
Tip size 17thou

Clean up and thinning

Clean up all equipment with water.

PaintPlus Easy Sand may be thinned to avoid exceeding application rates. Up to 50mls of water per litre may be added for this purpose.

Excessive thinning will lengthen drying times and have a detrimental impact on opacity and handling characteristics.