



# Fence Guard Exterior Acrylic

Fence Guard is a 100% acrylic specifically designed for fences. It can be applied directly to timber without the need of a primer or undercoat. It has a very low sheen level which is particularly suitable for coating rough sawn or textured surfaces.

## Product features

Self priming on timber  
Even coverage and consistent sheen  
High opacity

## Typical substrates

Fences & gates  
Timber  
Fibre Cement  
Existing waterbased paints in good condition  
Weathered concrete and brick

## Precautions

Fence Guard has been optimised for exterior application. Therefore it is not recommended for interior living areas.  
It is not suitable for use on face to face shutting surfaces such as windows and door frames.  
Do not apply to surfaces where water may pond.

## Environmental qualities

Manufactured in a carbon neutral certified facility – ISO 14064-1  
VOC < 1gm per litre EC07-13  
Ecolabel certified – Environmental Choice EC07-09  
Licence number 0703012

## Film properties

Heat resistance – 70°C maximum  
Water resistance – excellent  
Chemical resistance – resistant to household cleaners: avoid acids and alcohols  
Solvent resistance – poor resistance to strong solvents

## Colour and gloss

Gloss level and description – low sheen 7% at 60 degrees  
Colour range – Select range of COLORSTEEL® colours.

## Safety

Read label before use and keep out of reach of children.  
If medical advice is needed: have product container or label at hand.  
Wear protective clothing such as overalls, goggles and gloves and ventilate working areas.  
Wash any paint deposits off skin.  
If sanding wear face mask to avoid inhaling dust particles.

## Surface preparation

General preparation of the surface to be painted should be completed before commencing application.

All loose material must be removed and surface damage or imperfections made good.

The surface must be clean, dry and free of contaminants.

Areas with a build up of grime must be cleaned with sugar soap or quality equivalent.

## Application schedule

Touch dry 20 minutes

Re-coat time (minimum) 2 hours

Practical coverage 8–10 square meters per litre

Dry film thickness @ 10 square meters per litre  
38 microns

Required number of coats – 2

Application is not recommended if the surface and/or air temperature is less than 10°C or is liable to fall below 10°C during the drying period.

## Application methods

Good quality paint or cutting in brush

Medium nap roller – 12mm-14mm

Airless spray minimum 133 bars (2,000lb/sq in)

Tip size 17 thou

## Clean up and thinning

Clean up all equipment with water.

In warm and/or low humidity, Fence Guard may be thinned by the addition of up to 50mls of water per litre.

Hot weather thinners may be added during very hot weather at the rate of up to 50mls per litre.

## Disposal

Return any unused product to a PaintPlus stockist for recycling. If this is impractical or the residual paint is contaminated it may be left to dry by leaving the lid off the container.

Dispose with refuse if permitted by local municipal. Paint containers are reusable for non-food purposes and recyclable in areas where recycling and collection facilities are available.