



Easy Flow Low Sheen Acrylic

Easy Flow is an interior wall paint that has been optimized for marking resistance and ease of application. It flows beautifully to produce a high quality smooth finish. The low gloss level of Easy Flow means it can be used as ceiling paint in areas of low incidental light. Most surface marks may be removed with a soft cloth and a mild liquid detergent solution.

Product features

- Burnish resistant – resists marking
- Toughened film – cleanable
- No roller spatter – reduces clean ups
- Mould and fungi growth resistant – suitable for open plan kitchens, laundries
- Low odour – reoccupy times reduced

Typical areas of use

- General living areas
- Low traffic commercial areas
- Ceilings

Precautions

Easy Flow is formulated from an exterior grade pure acrylic. It will withstand exterior weather conditions but has been optimised for interior application. Therefore it is not recommended for exterior use.

Environmental qualities

- Manufactured in a carbon neutral certified facility – ISO 14064-1
- VOC 1gms per litre EC07-13
- Ecolabel certified – Environmental Choice EC07-13 Licence number 0703012

Film properties

- Heat resistance – 70°C maximum
- Water resistance – good – suitable for open plan kitchen areas
- Abrasion resistance – excellent – 650 scrub cycles - ASTM D2486
- Chemical resistance – resistant to household cleaners: avoid acids and alcohols
- Solvent resistance – poor resistance to strong solvents

Colour and gloss

- Gloss level and description – low sheen 7.5% @ 60 degrees
- Colour range – whites, pastels, mid tones, dark and extra bright colours

Safety

- Read label before use and keep out of reach of children.
- If medical advice is needed: have product container or label at hand.
- Wear protective clothing such as overalls, goggles and gloves and ventilate working areas.
- Wash any paint deposits off skin.
- If sanding wear face mask to avoid inhaling dust particles.

Surface preparation

General preparation of the surface to be painted should be completed before commencing application.

All loose material must be removed and surface damage or imperfections made good.

The surface must be clean, dry and free of contaminants.

Areas with a build up of grime must be cleaned with sugar soap or quality equivalent.

Previously painted enamel and polyurethane must be sanded to remove gloss.

Unpainted surfaces must have a coat of primer, sealer or undercoat applied.

Application schedule

Touch dry 20 minutes

Re-coat time (minimum) 2 hours

Practical coverage 10–12 square meters per litre

Dry film thickness @ 10 square meters per litre
40 microns

Required number of coats – 2

Application is not recommended if the surface and/or air temperature is less than 10°C or is liable to fall below 10°C during the drying period.

Primer/sealer requirements

New paper-faced wall board

Apply 1 coat of PaintPlus Easy Sand. When dry, sand and clean with a lint free cloth.

Previously painted surfaces

Prime repairs and bare areas with PaintPlus Easy Sand. When dry, sand and clean with a lint free cloth.

Enamel and polyurethane

Sand to remove gloss and apply 1 coat of PaintPlus Quick Prep. When dry, sand to required level of finish and clean with a lint free cloth.

Particle board and fibre board

Apply 1 coat of PaintPlus Quick Prep. When dry, sand to required level of finish and clean with a lint free cloth.

Application methods

Good quality paint or cutting in brush

Medium nap roller 10mm–12mm

Airless spray minimum 133 bars (2,000lb/sq in)

Tip size 17–19thou

Clean up and thinning

Clean up all equipment with water.

In warm and/or low humidity, Easy Flow may be thinned by the addition of up to 50mls of water per litre.