



Ultra Matt Flat Acrylic

Ultra Matt is an interior ceiling paint that has unique qualities. It is self priming which means no primer or sealer may be required if the surface is of good smooth finish. It is remarkably tough for a flat paint; resists marking, film damage and is cleanable. The tough film properties means it may be used as a wall finish in non service areas where a matt finish is desired.

Product features

- Burnish resistant – resists marking
- Toughened film – cleanable
- No roller spatter or drips and sags – no mess to clean up
- Low odour – reoccupy times reduced

Typical areas of use

- Ceilings
- Low traffic wall areas

Precautions

Ultra Matt is optimised for interior application and is not recommended for exterior use.

Environmental qualities

- Manufactured in a carbon neutral certified facility – ISO 14064-1
- VOC <1gms per litre EC07-13
- Ecolabel certified – Environmental Choice EC07-13
- Licence number 0703012

Film properties

- Heat resistance – 70°C maximum
- Water resistance – poor – not suitable for wet areas
- Chemical resistance – resistant to household cleaners: avoid acids and alcohols
- Solvent resistance – poor resistance to strong solvents

Colour and gloss

- Gloss level and description – flat 2% @ 60 degrees
- Colour range – white and pastel colours

Safety

- Read label before use and keep out of reach of children.
- If medical advice is needed: have product container or label at hand.
- Wear protective clothing such as overalls, goggles and gloves and ventilate working areas.
- Wash any paint deposits off skin.
- If sanding wear face mask to avoid inhaling dust particles.

Surface preparation

General preparation of the surface to be painted should be completed before commencing application.

All loose material must be removed and surface damage or imperfections made good.

The surface must be clean, dry and free of contaminants.

Areas with a build up of grime must be cleaned with sugar soap or quality equivalent.

Previously painted enamel and polyurethane must be sanded to remove gloss.

Unpainted surfaces must have a coat of primer, sealer or undercoat applied.

Application schedule

Touch dry 15 minutes

Re-coat time (minimum) 2 hours

Practical coverage 8–10 square meters per litre

Dry film thickness @ 10 square meters per litre
42 microns per coat

Required number of coats – 2

Application is not recommended if the surface and/or air temperature is less than 10°C or is liable to fall below 10°C during the drying period.

Primer/sealer requirements

Ultra Matt is self priming on plaster wall board.

Where a higher level of finish is required a primer is advantageous.

New paper-faced wall board - where required

Apply 1 coat of PaintPlus Easy Sand. When dry, sand and clean with a lint free cloth.

Previously painted surfaces

Prime repairs and bare areas with PaintPlus Easy Sand. When dry, sand and clean with a lint free cloth.

Enamel and polyurethane

Sand to remove gloss and apply 1 coat of PaintPlus Quick Prep. When dry, sand to required level of finish and clean with a lint free cloth.

Particle board and fibre board

Sand to required level of finish and clean with a lint free cloth.

Application methods

Good quality paint or cutting in brush

Medium nap roller – 12mm–14mm

Airless spray minimum 133 bars (2,000lb/sq in)

Tip size 17-21 thou

Clean up and thinning

Clean up all equipment with water.

On very dry substrates or, in warm and/or low humidity, Ultra Matt may be thinned by the addition of up to 50mls of water per litre.