paintplus

Scenic Flat Digital Green

PaintPlus Scenic Flat® Digital Green is a custom formulation for the scenic set artist. It has been specifically formulated to provide the necessary luminance values and colour saturation required for video keying effects.

Product features

Self priming on most substrates.

It dries to a flexible finish even when it is applied in thin coatings or highly diluted.

The sheen level of Scenic Flat® Digital Green is extremely low creating a very flat finish to minimise light reflection.

It is virtually odourless making it easy to work with and kind on the environment.

Typical Areas of Use

Canvas

Concrete

Brick

Fabric

Paper faced wallboard

Polystyrene

Plywood

Pressed chip board

Wood

Precautions

Not suitable for long term exterior applications

Colour and Gloss

Gloss level and description – flat 2% @ 60 degrees

Also available in Digital Blue

Application schedule

Drying and re-coat times are dependent on such factors as film thickness, atmospheric conditions, colour strength and dilution.

The general dry times are:

Touch dry 20 minutes

Re-coat time 30–60 minutes

Application is not recommended if the surface and/or air temperature is less than 10˚C or is liable to fall below 10˚C during the drying period.

TOITŪ NET CARBON ZERO ISO 14064-1 ORGANISATION

Eco Choice Aotearoa Licence No. 0703012

Product specifications change from time to time and may differ from those published.

PaintPlus Colour Systems Ltd
PO Box 101366
North Shore
Auckland 0745
+64 9 912 8474
info@paintplus.co.nz
www.paintplus.co.nz

Application methods

Good quality paint or cutting in brush Medium nap roller – 14mm–16mm

Airless spray minimum 133 bars (2,000lb/sq in) Tip size 15thou

Clean up and thinning

Clean up all equipment with water

Environmental qualities

Manufactured in a net carbon zero facility – ISO 14064-1

<5gms per litre EC07-18

Eco Choice Aotearoa certified – EC07-18 Licence number 0703012

Safety

Read label before use and keep out of reach of children.

Ingestion: Rinse mouth until clean, then drink plenty of water. Treat symptomatically. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Do NOT induce vomiting.

Skin: Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Get medical attention if irritation develops and persists.

Eye contact: Moderately irritating - wear splash proof goggles to protect eyes. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. If easy to do so remove contact lenses.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Phone NZ Chemcall Toll free 0800 243 622
or National Poisons Centre 0800 764 766

Australia Chemcall Toll free 1800 127 406

TOITŪ NET CARBON ZERO ISO 14064-1 ORGANISATION

Eco Choice Aotearoa
Licence No. 0703012

Product specifications change from time to time and may differ from those published.

PaintPlus Colour Systems Ltd
PO Box 101366
North Shore
Auckland 0745
+64 9 912 8474
info@paintplus.co.nz
www.paintplus.co.nz